

ONEMASTER TITANIUM APPLICATION & TECH SHEET GUIDE JAN 16 2016

Titanium wb is a multi-polymer elastomeric multi-surface penetrating surface guard concentrate w a 57 % active solid content.

Titanium wb in concentrate is applicable for matte- porous surfaces including Concrete pavers, polished concrete & all natural stone, masonry and wood.

****Performance testing is mandate prior to actual project application to insure desired results are always achieved.****

Titanium wb concentrate will allow 25 % h2o added and can be applied in thin even coats on numerous surfaces which allow Titanium to absorb with great leveling properties if adequate absorbency is available.

Polished Concrete with or without epoxy or densified if sanded and providing adequate absorbency with Titanium concentrate with 25% added water will burnish to a mirror reflection.

Titanium concentrate when cut with 25 % h2o average coverage testing has been 700-3000 ft. contingent on surface absorption.

For surfaces desiring a harder mirror finish apply Titanium with a pre-wet wrung out damp micro=fiber applicator in thin wet even coats allowing to completely dry with zero tack.

Using a black heat hogs hair pad burnish 1-2 coats burnishing in between coats and burnish 1 time last with green 3000# diamond impregnated pad for maximum abrasion, oil, gloss performance.

ONEMASTER TITANIUM was created by 40 yrs. R&D for professional application only.

ONEMASTER TITANIUM is water based global safe product with low odor & global shipping.

There are no expressed or implied warranties.

It is the responsibility of the Applicator/End/User to insure desired results have been achieved prior to actual project application.

Manufacturers only responsibility is to replace product for actual application area only if product is proven to be defective.

DISTRIBUTION & TECH SUPPORT ADVICE: 866-300-2344/CERTIFIED DISTRIBUTOR.